Material Safety Data Sheet

May be used to comply with OSHA=S Hazard Communication Standard 29 CFR 2910.1200. Standard must be consulted for specific requirements.

U.S. DEPARTMENT OF LABOR

Occupational Safety and Health (Non-Mandatory Form) Form Approved OMB No. 1218-0072

Identity (As Used on Label and List) #202 Big D Fire D On	Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.								
Section I									
Manufacturer=s Name Big D Industries, Inc.	Emergency Telephone Number (800) 535-5053 (800) 654-4752								
Address (number, Street, City, State, and ZIP Code) 5620 S. W. 29th Street (73179)	Telephone Number for Information (800) 654-4752 (405) 682-2541								
P. O. Box 82219	Date Prepared 01/01/2007								
Oklahoma City, OK 73148	Signature of Preparer (optional)								
Section II - HMIS Rating									
Health 1 Flammability	4	Reactivity	1						
Section III - Hazardous Ingredients/Identity Information									
Hazardous Components (Specific Chemical Identity: Common Name(s)) OSHA PEL ACGIH TLV Other Limits %(optional)									
Acetone CAS #67-64-1		500 ppm	500 ppm	-					
Amyl Acetate CAS #628-63-7	100 ppm	100 ppm	-						
Ethyl Acetate CAS #141-78-6	400 ppm 400 ppm								
Liq. Petrole\um Gas - CAS #68476-85-7	1000 ppm	1000 ppm							
Section IV - Physical/Chemical Cha	racteristics								
Boiling Point	-44 - 135 ⁰ F Conc.	Specific Gravity	$y (H_2O = 1) 0.5677$		N/E				
Vapor Pressure (mm Hg.)	N/E	Melting Point		N/A					
Vapor Density (AIR = 1)	>1	Evaporation Rate	Evaporation Rate		<1				
Solubility in Water: Slight									
Appearance and Odor: Produces fine mist with pleasant fragrance. Liquid is transparent.									
Section V - Fire and Explosion Haz	ard Data								
Flash Point (Method Used)		mmable Limits N/A		LEL 1.8%	UEL 12.8				
Extinguishing Media Carbon dioxide, dry foam, water spray									
Special Fire Fighting Procedures Self contained air supply suggested.									
Unusual Fire and Explosion Hazards Keep containers cool (below 130°F) to avoid bursting.									

Section VI - Reactivity Data								
Stability	Unstable		Conditions to Avoid: None					
	Stable	X						
Incompatibility (Materials to Avoid): Avoid contact with strong oxidizing agents such as nitric acid.								
Hazardous Decomposition or Byproducts: None								
Hazardous Polymerization	May Occur		Conditions to Avoid: None					
	Will Not Occur	X						
Section VII - Health Hazard Data								
Route(s) of Entry:	Inhalation? Yes	Skin?	Yes Ingestion? Yes					
Health Hazards (Acute and Chronic):								
Acute - Propellant is an asphyxiant and may exhibit properties at high concentrate. Chronic - Unconsciousness								
Carcinogenicity: NTP? No IARC Monographs? No OSHA Regulated? No								
Signs and Symptoms of Exposure: Skin - possible frostbite burn. Eyes - burning sensation. Inhalation - Headache, nausea, disorientation.								
Medical Conditions Generally Aggravated by Exposure: Emphysema								
Emergency and First Aid Procedures: Eye contact: flush with large amounts of water. May cause corneal damage on prolonged contact. Seek medical attn.								
Ingestion: Do not give anything by mouth to an unconscious person. Seek Medical attn. Inhalation: remove person to fresh air . Administer artificial respiration if not breathing. Seek medical attn.								
Section VIII - Precautions for Safe Handling and Use								
Steps to be Taken in Case Material is Released or Spilled:								
If container is ruptured and begins to leak, place in a well ventilated area and eliminate all ignition sources.								
Waste Disposal Method: do not discard empty container in incinerator or fire. Dispose of in accordance with Local, State, and Federal regulations.								
Precautions to be Taken in Handling and Storing: Store in cool area away from heat or open flame. Do not store above 130°F as containers may burst								
releasing the highly flammable propellant. AStore as Level Aerosol (NFPA 30B)								
Other precautions: In case of rupture, ventilate to prevent concentrations from reaching flammable levels. Note: any copies or redistribution of this M.S.D. Sheet must not be modified in any way.								
Section IX - Control Measures								
Respiratory Protection (Specify Type): Self contained breathing apparatus.								
Ventilation			Local Exhaust:: Doors & windows open Special N/A					
			Mechanical (General) Fan	Other N/A				
Protective Gloves: R	Subber or plastic for prole	onged conta	Eye Protection: Safety goggles for splash protection					
Other Protective Clothing or Equipment: Eye wash/shower facility nearby								
Work/Hygienic Practices: Good housekeeping practices. Avoid skin/eye contact.								

N.A. = Not Applicable N.D. - Not Determined Page 2 N/E - Not Established OSHA 174, Sept. 1985